

# ENTRY LEVEL DRYING CABINET

## DRI-CAB

**3 YEAR WARRANTY\*\***

**CE CERTIFIED**  
BY CERTIFICATION EXPERTS  
THE NETHERLANDS

Dry your screens securely in the 10 screen Dri-Cab. Powered fan with filtered air flow can have your screens ready for exposure, in as little as **60 MINUTES!\*\***



**VDC-2331**  
Holds (10) 23" X 31"  
(58 X 79cm) screens

- RELIABLE** 3 Year Warranty
- CAPACITY** Holds ten (10) 23" x 31" (58 x 79 cm) screens of any type
- POWERFUL** One (1) 91-113 CFM (2.6-3.2 CMM) air flow blower
- PRECISE** Light tight design prevents screen exposure
- EFFECTIVE** Screens sit horizontal on removable shelves (angled to provide edge contact only)
- SECURE** One (1) sealed latching door
- FAST** Dries emulsion as quickly as 60 minutes\*\*
- EASY** Simple to clean or replace filtered air intake

### Options

- Stainless steel shelves for rustproof drying
- 120v, 200v or 240v
- Mount rails for E-100, E-1000 or E-200
- Assembly



**E2-2128-VDC**  
E-200 w/ Drying cabinet



Easily replaceable filter keeps dust and other contaminants away from your screens.



| Unassembled Shipping |         | Assembled Shipping (crated) |         |
|----------------------|---------|-----------------------------|---------|
| Dimensions           | Weight  | Dimensions                  | Weight  |
| 43" x 29" x 9"       | 121 lbs | 43" x 35" x 40"             | 212 lbs |
| 34" x 29" x 8"       | 15 lbs  |                             |         |

**Questions? CALL 800-935-2121**



# Exposing Units

## Technical Specifications



|  | E200-2128 (LED)<br>E100-2128 (Fluorescent)   | E200-2331 (LED)<br>E100-2331 (Fluorescent)   | E2-2536 (LED)<br>E1-2536 (Fluorescent)   | E2-5236 (LED)<br>E1-5236 (Fluorescent)   |
|--|--|--|--|--|
| Overall Warranty                             | 3 Year   | 3 Year   | 3 Year   | 3 Year   |
| Maximum Screen Size                          | 21" x 28" (53 x 71 cm)   | 23" x 31" (56 x 78 cm)   | 25" x 36" (63 x 91 cm)   | 52" x 36" (132 x 91 cm)<br>or (2) 25" x 36" (63 x 91 cm)   |
| Image Area                                   | 15" x 18" (38 x 45 cm)   | 16" x 33" (58 x 83 cm)   | E2 - 24" x 36" (61 x 91 cm)<br>E1 - 18" x 27" (45 x 68 cm)   | E2 - 46" x 36" (116 x 91 cm)<br>E1 - 47" x 27" (119 x 68 cm)   |
| Bulbs (LED)                                  | Qty. (3) 18" (61 cm)<br>LED light bars   | Qty. (3) 30" (76 cm)<br>LED light bars   | Qty. (6) 30" (76 cm)<br>LED light bars   | Qty. (12) 30" (76 cm)<br>LED light bars  |
| Bulbs (Fluorescent)                          | Qty. (4) 20 watt T12-BL,<br>black UV   | Qty. (6) 40 watt<br>F28T12 BLHO, Black UV<br>fluorescent 28" (71cm) long   | Qty. (6) 47 watt<br>F7761T2 BLC, Black UV<br>fluorescent 30.5" (78cm) long   | Qty. (14) 47 watt<br>F7761T2 BLC, Black UV<br>fluorescent 30.5" (78cm) long  |
| Vacuum Pump,<br>Oil-less Diaphragm           | 1/16 HP<br>24 hg Max   | 1/16 HP<br>24 hg Max   | 1/4 HP High Output<br>23 Hg Max  | 1/4 HP High Output<br>23 Hg Max  |
| Power & Plug Spec<br>International Available | 120V 3.5A<br>NEMA 5-15P plug<br>240V 2A<br>NEMA 6-15P plug   | 120V / 60 HZ / 3.5A<br>NEMA 5-15P<br>240V / 50/60 HZ / 2A<br>NEMA 6-15P  | 120V / 60 HZ / 3.5A (E2-2536)<br>120V / 60 HZ / 3.5A (E1-2536)<br>NEMA 5-15P<br>240V / 50/60 HZ / 2A<br>NEMA 6-15P                 | 120V / 60 HZ / 6.5A (E2-5236)<br>120V / 60 HZ / 8A (E1-5236)<br>NEMA 5-15P<br>240V / 50/60 HZ / 4A<br>NEMA 6-15P                     |
| Overall Depth x<br>Width x Height            | Lid Closed<br>35.75" x 34.75" x 14"<br>(83 x 88 x 36 cm)<br>Lid Open<br>35.75" x 34.75" x 28"<br>(83 x 88 x 71 cm) | Lid Closed<br>41.6 x 36.2 x 48.3"<br>(105.7 x 92 x 122.7 cm)<br>Lid Open<br>41.6 x 36.2 x 68.2"<br>(105.7 x 92 x 173 cm) | Lid Closed<br>38.3" x 49.3" x 44.5"<br>(97.3 x 125.3 x 113.1 cm)<br>Lid Open<br>38.3" x 49.3" x 73.7"<br>(97.3 x 125.3 x 187.3 cm) | Lid Closed<br>65.3" x 49.3" x 44.5"<br>(165.8 x 125.3 x 113.1 cm)<br>Lid Open<br>65.3" x 49.3" x 73.7"<br>(165.8 x 125.3 x 187.3 cm) |
| Overall Weight - Uncrated                    | 100 lbs (45.4 kg)  | 180 lbs (81.6 kg)  | Call for details   | Call for details   |
| Shipping Weight*                             | 223 lbs (101 kg)<br>w/ Utility Cart (UC-1000)<br>483 lbs (219 kg)  | 386 lbs (175 kg)<br>w/ drying cabinet VDC253610<br>570 lbs (259 kg)  | Call for details   | Call for details   |
| Shipping Dimensions*                         | 43" x 43" x 17"<br>(109 x 109 x 43 cm)<br>w/ Utility Cart (UC-1000)<br>43" x 43" x 35"<br>(109 x 109 x 89 cm)      | 48" x 45" x 47"<br>(122 x 114.3 x 79 cm)<br>w/ drying cabinet VDC253610<br>49" x 45" x 49"<br>(124 x 114 x 124 cm)       | Call for details   | Call for details   |

# Drying Cabinets

## Technical Specifications



|  | Dri-Cab   | Dri-Vault - Drying Cabinets  |  |  |
|--|---|--|--|--|
|  | VDC-2331  | VDC-253610   | VDC-2536-24  | VDC-513610   |
| Defect Warranty                              | 3 Year  | 3 Year   | 3 Year   | 3 Year   |
| Maximum # of Screens                         | 10 @ maximum size   | 10 @ maximum size  | 24 @ maximum size                                  | (10) @ 51" x 36" / (20) @ 25" x 36"                  |
| Maximum Screen Size                          | 23" x 31" x 1.625"<br>(58.4 x 78.7 x 4.12 cm)   | 25" x 36" x 1.625"<br>(63.5 x 91.4 x 4.12 cm)  | 25" x 36" x 1.625"<br>(63.5 x 91.4 x 5.7 cm)       | (10 screens) @ 51" x 36"<br>(20 screens) @ 25" x 36" |
| Smallest Screen Width                        | 16" (46 cm)   | 18" (46 cm)  | 18" (46 cm)  | No minimum due to adjustable center tree             |
| Blower (Free Air)                            | 113 CFM (3.2 CMM)   | 177 CFM (5 cmm) <u>120v</u> or<br>290 CFM (8.2cmm) <u>240volt</u>  | 580 CFM (16.4 CMM)                                 | 290 CFM (8.2 CMM)                                    |
| Overall Depth x Width x Height               | 36" x 26" x 32" (91 x 66 x 81 cm)   | 39.5" x 34.75" x 32"   | 39.5" x 34.75" x 81"                               | 37.9" x 62.5" x 32.3"                                |
| Heater Wattage                               | N/A   | 1,250 Watts 120 Volts or<br>1,550 Watts 240 Volts  | 3,100 Watts 240 Volts                              | 1,550 Watts @ 240 Volts                              |
| Power & Plug Spec<br>International Available | 120V / 1A / 1 Ph. / 60 HZ /<br>NEMA 5-15P plug<br>or<br>240V / 1A / 1 Ph. / 50/60 HZ /<br>NEMA 6-15P plug | 120V / 10A / 1 Ph. / 60 HZ /<br>NEMA 5-15P plug<br>or<br>240V / 6A / 1 Ph. / 50/60 HZ /<br>NEMA 6-15P plug | 240V / 16A / 1 Ph. / 50/60 HZ /<br>NEMA 6-20P plug | 240V / 6A / 1 Ph. / 50/60 HZ /<br>NEMA 6-15P plug    |
| Shipping Weight (Assembled)*                 | 212 lbs (55.3 kg)   | 367 lbs (166.5 kg)   | 670 lbs (303 kg)                                   | 573 lbs (277 kg)                                     |
| Shipping Dimensions (Assembled)*             | 43" x 35" x 40"<br>(110 x 89 x 102 cm)  | 43" x 43" x 48"<br>(109 x 109 x 122 cm)  | 43" x 43" x 84"<br>(109 x 109 x 213 cm)            | 69" x 48" x 48"<br>(175.3 x 122 x 122 cm)            |
| Shipping Weight (Unassembled)*               | Box # 1 - 121 lbs (55 kg)<br>Box # 2 - 15 lbs (6.8 kg)  | N/A  | N/A  | N/A  |
| Shipping Dimensions (Unassembled)*           | Box # 1 - 43" x 29" x 9" (110 x 74 x 23 cm)<br>Box # 2 - 34" x 29" x 8" (87 x 74 x 21 cm)                 | N/A  | N/A  | N/A  |

\*All shipping weights and dimensions are for continental US shipping only. Call for other shipping specifications. Ex-works from Allentown PA.

1 in = 2.54 cm  
1 lb = 0.454 kg

Questions? CALL 800-935-2121